



## ZODZ.E167901 - POSITIONING DEVICES

## Positioning Devices

See General Information for Positioning Devices

## JEONO CO LTD

E167901

641 AEGIBONG-RO TONGJIN-EUP

GIMPO-SI, GYEONGGI-DO 415-862 REPUBLIC OF KOREA

## Metallic Cable Ties Investigated to ANSI/UL 62275

Cat. No.	Type Dsg.	Bundle Diam., mm(in.)		Loop Tensile Str., N (lbf)	Operating Temp., °C(°F)		Resistant to UV Light	Plenum Rating	Also Classified to [^] IEC 62275 and EN 62275
		Min	Max		Min	Max			
JSFT1000H-XXX	2	12.7 (0.50)	304 (11.97)	1112 (250)	-60 (-76)	165 (329)	Yes	-	-
JSFT1000S-XXX	2	12.7 (0.50)	304 (11.97)	445 (100)	-60 (-76)	165 (329)	Yes	-	-
JSFT1100EH-XXX	2	25.4 (1.00)	305 (12.01)	1332 (299)	-60 (-76)	165 (329)	Yes	-	-
JSFT125S-XXX	2	12.7 (0.50)	25 (0.98)	445 (100)	-60 (-76)	165 (329)	Yes	-	-
JSFT150S-XXX	2	12.7 (0.50)	35 (1.38)	445 (100)	-60 (-76)	165 (329)	Yes	-	-
JSFT200H-XXX	2	12.7 (0.50)	51 (2.01)	1112 (250)	-60 (-76)	165 (329)	Yes	-	-
JSFT200S-XXX	2	12.7 (0.50)	51 (2.01)	445 (100)	-60 (-76)	165 (329)	Yes	-	-
JSFT260H-XXX	2	12.7 (0.50)	69 (2.72)	1112 (250)	-60 (-76)	165 (329)	Yes	-	-
JSFT260S-XXX	2	12.7 (0.50)	69 (2.72)	445 (100)	-60 (-76)	165 (329)	Yes	-	-
JSFT360H-XXX	2	12.7 (0.50)	102 (4.02)	1112 (250)	-60 (-76)	165 (329)	Yes	-	-
JSFT360S-XXX	2	12.7 (0.50)	102 (4.02)	445 (100)	-60 (-76)	165 (329)	Yes	-	-

**Cookies on UL**  
We use cookies to  
personalize content  
and ads, to provide  
social media features  
and to analyze our  
traffic. We also share  
information about your  
use of our site with our  
social media  
advertising and  
analytics partners...

**JSFT200H-XXX**  
**JSFT200S-XXX**  
**JSFT260H-XXX**  
**JSFT260S-XXX**  
**JSFT360H-XXX**  
**JSFT360S-XXX**  
Learn More

Cookie Settings

✓ Accept



<b>J-202 (R18-202)</b>	21	2 (0.08)	51 (2.01)	80 (18)	-40 (-40)	85 (185)	-40 (-40)	-	-	V-2	-
<b>J-203 (R40-203)</b>	21	2 (0.08)	51 (2.01)	180 (40)	-40 (-40)	85 (185)	-40 (-40)	-	-	V-2	-
<b>J-250</b>	21	2 (0.08)	64 (2.52)	220 (49)	-40 (-40)	85 (185)	-40 (-40)	-	-	V-2	-
<b>J-270</b>	21	3 (0.12)	73 (2.87)	400 (90)	-20 (-4)	85 (185)	0 (32)	-	-	V-2	-
<b>J-300</b>	21	2 (0.08)	76 (2.99)	220 (49)	-40 (-40)	85 (185)	-40 (-40)	-	-	V-2	-
<b>J-303 (R40-303)</b>	21	2 (0.08)	77 (3.03)	180 (40)	-40 (-40)	85 (185)	-40 (-40)	-	-	V-2	-
<b>J-370 (R120-370)</b>	21	15 (0.59)	102 (4.02)	540 (121)	-40 (-40)	85 (185)	-40 (-40)	-	-	V-2	-
<b>J-373</b>	21	2 (0.08)	102 (4.02)	220 (49)	-40 (-40)	85 (185)	-40 (-40)	-	-	V-2	-
<b>J-450 (R175-450)</b>	21	35 (1.38)	127 (5.00)	800 (180)	-40 (-40)	85 (185)	-40 (-40)	-	-	V-2	-
<b>J-530 (R175-530)</b>	21	35 (1.38)	152 (5.98)	800 (180)	-40 (-40)	85 (185)	-40 (-40)	-	-	V-2	-
<b>J-540EH (R250-540EH)</b>	21	35 (1.38)	150 (5.91)	1150 (259)	-40 (-40)	85 (185)	-40 (-40)	-	-	V-2	-
<b>JLTW-540</b>	21	35 (1.38)	150 (5.91)	1150 (259)	-40 (-40)	85 (185)	-40 (-40)	Yes	-	V-2	-
<b>JMT-1M (RMT18-1M)</b>	21	6 (0.24)	19 (0.75)	80 (18)	-40 (-40)	85 (185)	-40 (-40)	-	-	V-2	-
<b>JMT-2M (RMT18-2M)</b>	21	6 (0.24)	51 (2.01)	80 (18)	-40 (-40)	85 (185)	-40 (-40)	-	-	V-2	-
<b>JMTW-1M (WMT18-1M)</b>	21	6 (0.24)	19 (0.75)	80 (18)	-40 (-40)	85 (185)	-40 (-40)	Yes	-	V-2	-
<b>JMTW-2M</b>	21	6 (0.24)	51 (2.01)	80 (18)	-40 (-40)	85 (185)	-40 (-40)	-	-	V-2	-
<b>JV-100</b>	21	2 (0.08)	22 (0.87)	80 (18)	-40 (-40)	85 (185)	-40 (-40)	-	-	V-0	-

Learn More

<b>JV-140</b>	21	2 (0.08)	35 (1.38)	180 (40)	-40 (-40)	85 (185)	-40 (-40)	-	-	V-0	-
<b>JV-200</b>	21	2 (0.08)	48 (1.89)	220 (49)	-40 (-40)	85 (185)	-40 (-40)	-	-	V-0	-
<b>JV-270</b>	21	3 (0.12)	73 (2.87)	400 (90)	-40 (-40)	85 (185)	0 (32)	-	-	V-0	-
<b>JV-300</b>	21	2 (0.08)	76 (2.99)	220 (49)	-40 (-40)	85 (185)	-40 (-40)	-	-	V-0	-
<b>JV-370</b>	21	15 (0.59)	102 (4.02)	540 (121)	-40 (-40)	85 (185)	-40 (-40)	-	-	V-0	-
<b>JV-450</b>	21	35 (1.38)	127 (5.00)	800 (180)	-20 (-4)	85 (185)	-40 (-40)	-	-	V-0	-
<b>JW-100 (W18-100)</b>	21	2 (0.08)	22 (0.87)	80 (18)	-40 (-40)	85 (185)	-40 (-40)	Yes	-	V-2	-
<b>JW-140 (W40-140)</b>	21	2 (0.08)	35 (1.38)	180 (40)	-40 (-40)	85 (185)	-40 (-40)	Yes	-	V-2	-
<b>JW-162 (W18-162)</b>	21	2 (0.08)	40 (1.57)	80 (18)	-40 (-40)	85 (185)	-40 (-40)	Yes	-	V-2	-
<b>JW-200 (W50-200)</b>	21	2 (0.08)	48 (1.89)	220 (49)	-40 (-40)	85 (185)	-40 (-40)	Yes	-	V-2	-
<b>JW-202 (W18-202)</b>	21	2 (0.08)	51 (2.01)	80 (18)	-40 (-40)	85 (185)	-40 (-40)	Yes	-	V-2	-
<b>JW-203 (W40-203)</b>	21	2 (0.08)	51 (2.01)	180 (40)	-40 (-40)	85 (185)	-40 (-40)	Yes	-	V-2	-
<b>JW-250 (W50-250)</b>	21	2 (0.08)	64 (2.52)	220 (49)	-40 (-40)	85 (185)	-40 (-40)	Yes	-	V-2	-
<b>JW-270 (W40-270)</b>	21	3 (0.12)	73 (2.87)	400 (90)	-40 (-40)	85 (185)	-20 (-4)	Yes	-	V-2	-
<b>JW-300 (W50-300)</b>	21	2 (0.08)	76 (2.99)	220 (49)	-40 (-40)	85 (185)	-40 (-40)	Yes	-	V-2	-
<b>JW-300EH (W40-303)</b>	21	20 (0.79)	70 (2.76)	1150 (259)	-40 (-40)	85 (185)	-40 (-40)	Yes	-	V-2	-
<b>JW-303 (W40-303)</b>	21	2 (0.08)	77 (3.03)	180 (40)	-40 (-40)	85 (185)	-40 (-40)	Yes	-	V-2	-

<b>JW-370 (W120-370)</b>	21	15 (0.59)	102 (4.02)	540 (121)	-40 (-40)	85 (185)	-40 (-40)	Yes	-	V-2	-
<b>JW-373 (W50-373)</b>	21	2 (0.08)	102 (4.02)	220 (49)	-40 (-40)	85 (185)	-40 (-40)	Yes	-	V-2	-
<b>JW-400EH</b>	21	20 (0.79)	102 (4.02)	1150 (259)	-40 (-40)	85 (185)	-40 (-40)	Yes	-	V-2	-
<b>JW-450 (W175-450)</b>	21	35 (1.38)	127 (5.00)	800 (180)	-40 (-40)	85 (185)	-40 (-40)	Yes	-	V-2	-
<b>JW-530 (W175-530)</b>	21	35 (1.38)	152 (5.98)	800 (180)	-40 (-40)	85 (185)	-40 (-40)	Yes	-	V-2	-
<b>JW-540EH (W250-540EH)</b>	21	35 (1.38)	150 (5.91)	1150 (259)	-40 (-40)	85 (185)	-40 (-40)	Yes	-	V-2	-

XXX - Maybe represented by 304 or 316, means the cable tie was made by 304 or 316 stainless steel

Trademark and/or Tradename:  **JEONO®** **JEONO®**

Last Updated on 2019-04-22

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions:  
1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2019 UL LLC"

We use cookies to  
personalize content  
and ads, to provide  
social media features  
and to analyze our  
traffic. We also share  
information about your  
use of our site with our  
social media,  
advertising and  
analytics partners..  
[Learn More](#)

> [Cookie Settings](#)

✓ [Accept](#)