

# ZODZ.E167901 - Positioning Devices

## Positioning Devices

**JEONO CO LTD**

641 Aegibong-ro Tongjin-eup

Gimpo-si, Gyeonggi-do 415-862 Republic of Korea

E167901

### Metallic Cable Ties Investigated to ANSI/UL 62275

Cat. No.	Type Dsg.	Bundle Dia. mm		Loop Tensile Str. N	Operating Temp. °C		Resistant to UV Light	Plenum Rating	Also Classified to [^] IEC 62275 and EN 62275
		Min	Max		Min	Max			
JSFT1000H-XXX	2	12.7	304	1112	-	165	Y	-	-
JSFT1000S-XXX	2	12.7	304	445	-	165	Y	-	-
JSFT1100EH-XXX	2	25.4	305	1332	-	165	Y	-	-
JSFT125S-XXX	2	12.7	25	445	-	165	Y	-	-
JSFT150S-XXX	2	12.7	35	445	-	165	Y	-	-
JSFT200H-XXX	2	12.7	51	1112	-	165	Y	-	-
JSFT200S-XXX	2	12.7	51	445	-	165	Y	-	-
JSFT260H-XXX	2	12.7	69	1112	-	165	Y	-	-
JSFT260S-XXX	2	12.7	69	445	-	165	Y	-	-
JSFT360H-XXX	2	12.7	102	1112	-	165	Y	-	-
JSFT360S-XXX	2	12.7	102	445	-	165	Y	-	-
JSFT440EH-XXX	2	25.4	102	1332	-	165	Y	-	-
JSFT520H-XXX	2	12.7	152	1112	-	165	Y	-	-
JSFT520S-XXX	2	12.7	152	445	-	165	Y	-	-
JSFT600EH-XXX	2	25.4	152	1332	-	165	Y	-	-
JSFT680H-XXX	2	12.7	203	1112	-	165	Y	-	-
JSFT680S-XXX	2	12.7	203	445	-	165	Y	-	-
JSFT760EH-XXX	2	25.4	203	1332	-	165	Y	-	-
JSFT840H-XXX	2	12.7	254	1112	-	165	Y	-	-
JSFT840S-XXX	2	12.7	254	445	-	165	Y	-	-
JSFT920EH-XXX	2	25.4	254	1332	-	165	Y	-	-

JSHT1000H-XXX	2	12.7	304	1470	-	165	Y	-	-
JSHT1000S-XXX	2	12.7	304	890	-	165	Y	-	-
JSHT1100EH-XXX	2	25.4	305	2000	-	165	Y	-	-
JSHT125S-XXX	2	12.7	25	890	-	165	Y	-	-
JSHT150S-XXX	2	12.7	35	890	-	165	Y	-	-
JSHT200H-XXX	2	12.7	51	1470	-	165	Y	-	-
JSHT200S-XXX	2	12.7	51	890	-	165	Y	-	-
JSHT260H-XXX	2	12.7	69	1470	-	165	Y	-	-
JSHT260S-XXX	2	12.7	69	890	-	165	Y	-	-
JSHT360H-XXX	2	12.7	102	1470	-	165	Y	-	-
JSHT360S-XXX	2	12.7	102	890	-	165	Y	-	-
JSHT440EH-XXX	2	25.4	102	2000	-	165	Y	-	-
JSHT520H-XXX	2	12.7	152	1470	-	165	Y	-	-
JSHT520S-XXX	2	12.7	152	890	-	165	Y	-	-
JSHT600EH-XXX	2	25.4	152	2000	-	165	Y	-	-
JSHT680H-XXX	2	12.7	203	1470	-	165	Y	-	-
JSHT680S-XXX	2	12.7	203	890	-	165	Y	-	-
JSHT760EH-XXX	2	25.4	203	2000	-	165	Y	-	-
JSHT840H-XXX	2	12.7	254	1470	-	165	Y	-	-
JSHT840S-XXX	2	12.7	254	890	-	165	Y	-	-
JSHT920EH-XXX	2	25.4	254	2000	-	165	Y	-	-
JSST1000H-XXX	2	12.7	304	1470	-60	300	Y	-	-
JSST1000S-XXX	2	12.7	304	890	-60	300	Y	-	-
JSST1100EH-XXX	2	25.4	305	2665	-60	300	Y	-	-
JSST125S-XXX	2	12.7	25	890	-60	300	Y	-	-
JSST150S-XXX	2	12.7	35	890	-60	300	Y	-	-
JSST200H-XXX	2	12.7	51	1470	-60	300	Y	-	-
JSST200S-XXX	2	12.7	51	890	-60	300	Y	-	-
JSST260H-XXX	2	12.7	69	1470	-60	300	Y	-	-
JSST260S-XXX	2	12.7	69	890	-60	300	Y	-	-
JSST360H-XXX	2	12.7	102	1470	-60	300	Y	-	-
JSST360S-XXX	2	12.7	102	890	-60	300	Y	-	-

<b>JSST440EH-XXX</b>	2	25.4	102	2665	-60	300	Y	-	-
<b>JSST520H-XXX</b>	2	12.7	152	1470	-60	300	Y	-	-
<b>JSST520S-XXX</b>	2	12.7	152	890	-60	300	Y	-	-
<b>JSST600EH-XXX</b>	2	25.4	152	2665	-60	300	Y	-	-
<b>JSST680H-XXX</b>	2	12.7	203	1470	-60	300	Y	-	-
<b>JSST680S-XXX</b>	2	12.7	203	890	-60	300	Y	-	-
<b>JSST760EH-XXX</b>	2	25.4	203	2665	-60	300	Y	-	-
<b>JSST840H-XXX</b>	2	12.7	254	1470	-60	300	Y	-	-
<b>JSST840S-XXX</b>	2	12.7	254	890	-60	300	Y	-	-
<b>JSST920EH-XXX</b>	2	25.4	254	2665	-60	300	Y	-	-

#### Nonmetallic Cable Ties Investigated to ANSI/UL 62275

Cat. No.	Type Dsg.	Bundle Dia. mm		Loop Tensile Str. N	Operating Temp. °C		Min. Install. Temp. °C	Resistant to UV Light	Plenum Rating	Also Classified to [^] IEC 62275 and EN 62275
		Min	Max		Min	Max				
<b>J-100 (R18-100)</b>	21	2	22	80	-40	85	-40	-	-	-
<b>J-1000</b>	21	80	305	800	-25	85	0	-	-	-
<b>J-140 (R40-140)</b>	21	2	35	180	-40	85	-40	-	-	-
<b>J-162 (R18-162)</b>	21	2	40	80	-40	85	-40	-	-	-
<b>J-200 (R50-200)</b>	21	2	48	220	-40	85	-40	-	-	-
<b>J-202 (R18-202)</b>	21	2	51	80	-40	85	-40	-	-	-
<b>J-203 (R40-203)</b>	21	2	51	180	-40	85	-40	-	-	-
<b>J-250</b>	21	2	64	220	-40	85	-40	-	-	-
<b>J-270</b>	21	3	73	400	-20	85	0	-	-	-
<b>J-300</b>	21	2	76	220	-40	85	-40	-	-	-
<b>J-303 (R40-303)</b>	21	2	77	180	-40	85	-40	-	-	-
<b>J-370 (R120-370)</b>	21	15	102	540	-40	85	-40	-	-	-
<b>J-373</b>	21	2	102	220	-40	85	-40	-	-	-
<b>J-450 (R175-450)</b>	21	35	127	800	-40	85	-40	-	-	-
<b>J-530 (R175-530)</b>	21	35	152	800	-40	85	-40	-	-	-
<b>J-540EH (R250-540EH)</b>	21	35	150	1150	-40	85	-40	-	-	-

<b>J-780</b>	21	80	229	800	-25	85	0	-	-	-
<b>JMT-1M (RMT18-1M)</b>	21	6	19	80	-40	85	-40	-	-	-
<b>JMT-2M (RMT18-2M)</b>	21	6	51	80	-40	85	-40	-	-	-
<b>JMTW-1M (WMT18-1M)</b>	21	6	19	80	-40	85	-40	Y	-	-
<b>JMTW-2M</b>	21	6	51	80	-40	85	-40	-	-	-
<b>JV-100</b>	21	2	22	80	-40	85	-40	-	-	-
<b>JV-140</b>	21	2	35	180	-40	85	-40	-	-	-
<b>JV-162</b>	21	2	40	80	-25	85	0	-	-	-
<b>JV-200</b>	21	2	48	220	-40	85	-40	-	-	-
<b>JV-202</b>	21	2	51	80	-25	85	0	-	-	-
<b>JV-250</b>	21	4	64	220	-25	85	0	-	-	-
<b>JV-270</b>	21	3	73	400	-40	85	0	-	-	-
<b>JV-300</b>	21	2	76	220	-40	85	-40	-	-	-
<b>JV-370</b>	21	15	102	540	-40	85	-40	-	-	-
<b>JV-373</b>	21	11	102	220	-25	85	-25	-	-	-
<b>JV-450</b>	21	35	127	800	-20	85	-40	-	-	-
<b>JV-530</b>	21	32	152	800	-25	85	-25	-	-	-
<b>JW-100 (W18-100)</b>	21	2	22	80	-40	85	-40	Y	-	-
<b>JW-1000</b>	21	80	305	800	-25	85	0	Y	-	-
<b>JW-140 (W40-140)</b>	21	2	35	180	-40	85	-40	Y	-	-
<b>JW-162 (W18-162)</b>	21	2	40	80	-40	85	-40	Y	-	-
<b>JW-200 (W50-200)</b>	21	2	48	220	-40	85	-40	Y	-	-
<b>JW-202 (W18-202)</b>	21	2	51	80	-40	85	-40	Y	-	-
<b>JW-203 (W40-203)</b>	21	2	51	180	-40	85	-40	Y	-	-
<b>JW-250 (W50-250)</b>	21	2	64	220	-40	85	-40	Y	-	-
<b>JW-270</b>	21	3	73	400	-40	85	-20	Y	-	-
<b>JW-300 (W50-300)</b>	21	2	76	220	-40	85	-40	Y	-	-

<b>JW-300EH</b>	21	20	70	1150	-40	85	-40	Y	-	-
<b>JW-303 (W40-303)</b>	21	2	77	180	-40	85	-40	Y	-	-
<b>JW-370 (W120-370)</b>	21	15	102	540	-40	85	-40	Y	-	-
<b>JW-373 (W50-373)</b>	21	2	102	220	-40	85	-40	Y	-	-
<b>JW-400EH</b>	21	20	102	1150	-40	85	-40	Y	-	-
<b>JW-450 (W175-450)</b>	21	35	127	800	-40	85	-40	Y	-	-
<b>JW-530 (W175-530)</b>	21	35	152	800	-40	85	-40	Y	-	-
<b>JW-780</b>	21	80	229	800	-25	85	0	Y	-	-

XXX - Maybe represented by 304 or 316, means the cable tie was made by 304 or 316 stainless steel

Trademark and/or Tradename:  **JEONO®** **JEONO®**

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2023 UL LLC."