

UL Product iQ™



ZODZ2.E167901 - Positioning Devices - Component

Positioning Devices - Component

See General Information for Positioning Devices - Component

JEONO CO LTD

E167901

641 AEGIBONG-RO TONGJIN-EUP

GIMPO-SI, GYEONGGI-DO 415-862 REPUBLIC OF KOREA


Positioning Devices Investigated to ANSI/UL 1565

Catalog No.	Maximum Use Temp °C(°F)
PVC Wiring Ducts (gray and ivory color) "JWDA Series"	
100 x 80 mm	50 (122)
20 x 35 mm	50 (122)
PVC Wiring Ducts (gray and ivory color) "JWDA Series"	
100 x 100 mm	50 (122)
25 x 40 mm	50 (122)
25 x 55 mm	50 (122)
25 x 60 mm	50 (122)
30 x 40 mm	50 (122)
30 x 60 mm	50 (122)
30 x 80 mm	50 (122)
40 x 100 mm	50 (122)
40 x 40 mm	50 (122)
40 x 60 mm	50 (122)
40 x 80 mm	50 (122)
60 x 100 mm	50 (122)
60 x 40 mm	50 (122)
60 x 60 mm	50 (122)

60 x 80 mm	50 (122)
80 x 100 mm	50 (122)
80 x 60 mm	50 (122)
80 x 80 mm	50 (122)
PVC Wiring Ducts (gray and ivory color) "JWDC Series"	
100 x 100 mm	50 (122)
20 x 35 mm	50 (122)
PVC Wiring Ducts (gray and ivory color) "JWDC Series"	
25 x 40 mm	50 (122)
25 x 60 mm	50 (122)
30 x 60 mm	50 (122)
30 x 80 mm	50 (122)
40 x 100 mm	50 (122)
40 x 60 mm	50 (122)
40 x 80 mm	50 (122)
60 x 100 mm	50 (122)
60 x 40 mm	50 (122)
60 x 60 mm	50 (122)
60 x 80 mm	50 (122)
80 x 100 mm	50 (122)
80 x 80 mm	50 (122)
ABS Wiring Ducts (gray and ivory color) "JWDH Series"	
100 x 100 mm, 100X100A	60 (140)
60 x 60 mm, 60X60A	60 (140)
ABS Wiring Ducts (gray and ivory color) "JWDH Series"	
30 x 60 mm, 30X60A	60 (140)
40 x 40 mm, 40X40A	60 (140)
40 x 60 mm, 40X60A	60 (140)
40 x 80 mm, 40X80A	60 (140)
60 x 80 mm, 60X80A	60 (140)

80 x 100 mm, 80X100A	60 (140)
80 x 60 mm, 80X60A	60 (140)
80 x 80 mm, 80X80A	60 (140)
PVC Wiring Ducts (gray and ivory color) "JWDN Series"	
20 x 35 mm	50 (122)
PVC Wiring Ducts (gray and ivory color) "JWDN Series"	
100 x 100 mm	50 (122)
25 x 40 mm	50 (122)
25 x 60 mm	50 (122)
30 x 60 mm	50 (122)
30 x 80 mm	50 (122)
40 x 100 mm	50 (122)
40 x 60 mm	50 (122)
40 x 80 mm	50 (122)
60 x 100 mm	50 (122)
60 x 40 mm	50 (122)
60 x 60 mm	50 (122)
60 x 860 mm	50 (122)
80 x 80 mm	50 (122)
PVC Wiring Ducts (gray and ivory color) "JWDO Series"	
20 x 35 mm	50 (122)
PVC Wiring Ducts (gray and ivory color) "JWDO Series"	
25 x 40 mm	50 (122)
25 x 60 mm	50 (122)
30 x 60 mm	50 (122)
30 x 80 mm	50 (122)
40 x 60 mm	50 (122)
40 x 80 mm	50 (122)
60 x 40 mm	50 (122)
60 x 60 mm	50 (122)

60 x 80 mm	50 (122)
80 x 80 mm	50 (122)

Marking: Company name, catalog or model number, the Recognized Component Mark,  and, if published with the product, the product's maximum and minimum operating temperature, minimum installation temperature if below 0°C, minimum and maximum bundle diameter, loop tensile strength, type designation and/or declared mechanical strength on the product or on the smallest unit container in which the product is packaged.

Last Updated on 2017-12-07

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions:

1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2020 UL LLC"